

AEON® PD Bearing Grease

High Temperature & Performance

Application

- AEON PD Grease is an extreme pressure, high temperature and performance grease providing optimum bearing performance and lubrication for use in positive displacement blowers & vacuum pumps
- Engineered for the Gardner Denver Legend Series and CycloBlower truck blowers

Usage & Performance

- Designed for severe operating conditions in a wide range of global applications
- Correct lubrication is critically important in maintaining long bearing life
- Avoid the risk of early bearing failure due to incompatible greases by using factory-specified AEON PD Grease
- To maintain the performance characteristics of AEON PD Grease, completely clean previously used greases from the blower as different types of grease may not be compatible
- For specific usage instructions, refer to the blower Operating and Maintenance Manual

Parameters & Features

- AEON PD Grease is formulated with anti-wear additives to maximize equipment life
- Contains rust inhibitors which provide excellent protection against rust and corrosion
- Provides superior protection in a wide operating temperature range of -40° F to 350° F



Experience Proven Results
with Gardner Denver —
the Leader in Durability,
Reliability and Efficiency



Experience Proven Results™

Genuine Gardner Denver AEON PD Bearing Grease

Legend Series

- Bearings on the drive end of the blower require grease lubrication every 500 hours of operation
- Lubricate bearings through grease fittings, as depicted in photo
- When re-greasing, the old grease will be forced out of the grease vents
- Keep the grease vents open at all times to prevent damage to the seals



CycloBlower Truck Blowers

- Bearings are recommended to be re-greased every 250 hours of operation
- The pressure relief fittings should be cleaned of all dirt and foreign material before lubricating bearings
- With a pressure or hand gun, fill bearing cavity with grease until it begins to come out of the grease relief fitting

PROPERTIES	AEON GREASE
NLGI Grade	2
Soap Type	Lithium Complex
Mineral Oil Viscosity	
cSt at 40° C	150
cSt at 100° C	13
SUS at 100° F	750
SUS at 210° F	70
ISO Viscosity Grade	150
Penetration at 23° C, worked	280
Dropping point, ASTM D 2265, ° F	475

AEON PD Bearing Grease

Order Information

Case of ten 14-oz. Cartridges 28H283



Gardner Denver®

www.GardnerDenverProducts.com mobilesolutions@gardnerdenver.com

Gardner Denver, Inc. 1800 Gardner Expressway, Quincy, IL 62305
Customer Service Department
Telephone: (800) 682-9868 FAX: (217) 221-8780

Member



©2009 Gardner Denver, Inc. Printed in U.S.A. PD-AEON-GREASE 1st Ed. 8/09
Supersedes GD-2-310



Please recycle after use.